

SNBC

Extraordinary
Value!

BTP-M280

Impact Receipt Printers



Preferred for POS Kitchen Printer Applications

The BTP-M280 produces either receipts or kitchen orders faster than other popular impact printers. Featuring trouble-free drop-and-print paper loading, it is adjustable to accommodate 76, 70, or 58mm paper rolls. Print is clear and precise, allowing you to print long-lasting receipts with coupons, rebates and specials. User defined graphic logos are easily downloaded with SNBC's free utility software.

- Dual Interface Standard – USB Interface is on the Main Board
- Serial, Parallel, Ethernet and Wireless WiFi Interface Options
- Two Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Stores and Prints Logo Images
- Extraordinary Reliability
- Everything Needed – Including Communications Cables – Included in the Box


BTP-M280A – Auto Cutter / Paper Take-up

BTP-M280B – Auto Cutter

BTP-M280D – Manual Tear



SNBC BTP-M280 Series Impact Receipt Printers



Drop and Print Paper Loading with Built-In Paper Width Selector



Built-In Wall Mount Capability and Optional Audio/Visual Print Messenger



Conceal the Power Supply in the Optional Power Supply Cover



Includes Everything Necessary in the Carton

Features

Proven impact printing technology preferred for POS kitchen printer applications.

- Everything You Need is in the Box
- Dual Interface / USB Interface is on the Main Board
- Serial, Parallel, Ethernet and Wireless WiFi Interface Boards Available
- Uses the Same Interface Boards as Other SNBC Printers
- Auto-Cutter with Selectable Full or Partial Cut (BTP-M280A and M280B)
- Two-Color Print – Uses Industry Standard ERC-38 Ribbon Cartridge
- Fast 4.7 Lines per Second Print Speed
- Drop and Print Paper Loading
- Built-In Wall Mount Capability
- Paper-End Sensor
- Adjustable Paper Near-End Sensor
- No Dip Switches
- Includes Starter Paper Roll, Paper Width Selector, Communications Cable, USB Cable, Power Adapter and Cord, Ribbon, CD-ROM with Drivers, Utilities and User's Manual

Optional Devices / Upgrades

Upgrade your printer with these easy-to-add options:

- Serial, Parallel, Ethernet and Wireless WiFi Interface Boards Are User Interchangeable
- Audio/Visual Print Messenger – For Noisy Kitchens – Alarm Sounds and Light Flashes When a New Order is Printed
- Power Supply Cover
- Powered USB Cable

Ports and Connectivity

- A Choice of Serial (Shown), Parallel, Ethernet or Wireless WiFi Daughter Boards Available
- B USB Interface on Main Board
- C Cash Drawer
- D DC 24V Power-In

Specifications

Print Speed:	19.6mm per Second / 4.7 Lines per Second
Characters Per Line –	Font A: 33 / 35 Font B: 40 / 42
Characters Size –	Font A: 9 x 9 Font B: 7 x 9
Paper Roll Type –	Width: 76±0.5mm, 69.5±0.5mm, 57.5±0.5mm Maximum Diameter: 83.0mm
Inking Supply:	ERC-38 Ribbon Cartridge (Black/Red)
Reliability –	MTBF: 300,000 Hours MCBF: 18,000,000 Lines Printhead Life: 150,000,000 Characters Cutter Life: 1,500,000 Cuts
Character Set:	Alphanumeric: 95 International: 32
Extended Graphic:	128 x 8 Page
Interpreter:	ESC/POS™
Interface:	USB, Serial/USB, Parallel/USB, Ethernet/USB, WiFi/USB
Driver:	Windows 98 / NT4.0 / 2000 / 2003 / XP / VISTA
Drawer Port:	One RJ-12 (+24VDC) (Maximum 2 Drawers – Supports Open/Close)
Data Buffer –	Receive Buffer: 8 KB RAM NV Bit Image Data: 128 KB User NV Memory: 8 KB
Power Supply:	AC 100 ~ 240 V, 50/60 Hz Adapter Included
Current/Power Usage:	1.5A / 36W
Operating Temperature:	40° ~ 114°F (5° ~ 45°C)
Operating Humidity:	20% ~ 90% RH (Non-Condensing)
Paper Cutting Method –	M280A/B: Auto-Cutter with Selectable Full or Partial Cut M280D: Manual Tear
Dimensions / Weight –	M280A: 6-5/16"W x 6-5/8"H x 11-3/4"D / 6.67 lbs. M280B: 6-5/16"W x 5-11/16"H x 9-5/8"D / 6.20 lbs. M280D: 6-5/16"W x 5-11/16"H x 9-5/8"D / 5.86 lbs.
Safety and EMI:	FCC, UL, CUL, CE, CB, GS, RoHS

